

SPECIFICATION OF BUTTERFLY GASKET SHEET



BF#350, BUTTERFLY COMPRESSED ASBESTOS RUBBER SHEET



BF#350 SIZE 1270X1270 mm.

Pressure : 4.0 Mpa Temperature: 350° C

COLOR : BLACK, RED

Main Material : Asbestos fiber and nature rubber.

Processing : Heat-Compressing in moulds

Application : Suitable for seal gasket materials for equipments, pipeline, flanges with solvent.

BUTTERFLY UNIVERSAL ASBESTOS COMPRESSION SHEET



BF#1500 SIZE 1270X1270 mm.

Pressure : 6.0 Mpa Temperature: 500° C

COLOR : BLACK

Main Material : High quality long fiber asbestos, special synthetic rubber, heat-resistant & chemical-resistant in organic filler

Processing : Compressing in moulds.

Applied Fluids : Water, hot water, high pressure steam, acid, alkali and salt solution, animal and plant oil, fuel oil, power oil, lubricating oil, natural gas, solvents, and liquefied petroleum gas and other gases.

Application : Applicable to all factories, power stations, oil refineries, steel mills, ship in the allocation of flanges, valves caps, and tank tower type, pressure vessels, heat exchangers, shell and covered part of the joint seal. (To achieve the performance of VALQUA No.#1500 & No.#1501.)

BUTTERFLY UNIVERSAL NON-ASBESTOS COMPRESSION SHEET

ไม่มีส่วนผสม ของแร่ใยหิน



BF#6500 SIZE 1270X1270 mm.

Pressure : 4.0 Mpa Temperature: 250° C

COLOR : BLUE

Main Material : Kevlar fiber (no harm to human and environment), synthetic oil-resistant rubber and heat-resistant filler.

Processing : Compressing and Vulcanize.

Max Temperature : 250°C

Max Pressure : 4.0MPa

Tensile Strength : 9.0-11.0MPa

Density : 1.65g/cm³

Application : Sealing gasket for equipments of automobile engine, motorcycle engine, diesel, internal-combustion engine, chemical industry, shipping industry and flanges of pipeline.